



Product Quotation

**Prepared For:
John Brown**

**Powder Springs Public Works
Powder Springs Georgia 30127**



**Prepared By:
JONATHAN JENKINS
WESPRO JCB (HL)
mobile:**

Image is for indicative purpose only and may not represent exact equipment being quoted



Standard Equipment

Standard Equipment and Features & Benefits related to this product are subject to change without notice

ENGINE	Tier IV Final compliant 48.3 SAE gross hp diesel engine, centrifugal dry type air cleaner. Water separator, spin-on oil filter, thermostart assist, antifreeze protection to -35 degrees F.
TRANSMISSION	Independent left and right track control. Hydraulic pumps drive integral track motors and gearbox. Two speed travel, 1.8 mph and 2.8 mph.
TRACKS	Rubber (optional steel) grease adjusted. Under carriage rollers 5 per side. Track width 15.75". Ground pressure 4.7 lbs per square inch. Ground clearance 12".
ELECTRICAL	12 volt, with 100 amp alternator, 410 CCA heavy duty battery. Waterproof wire harness connectors.
EXCAVATOR	Maximum dig depth with standard dipper 12' 7". Servo controls, SAE and ISO patterns both available on 55Z Compact Excavator with DPC -Dual Pattern Control system. Auxiliary circuit provides 23.7 GPM for JCB hydraulic breakers and other approved attachments. Dozer control. Boom swing left 70 degree, right 55 degree. Less excavator bucket. Double acting hydraulics optional fit.
CAB/CANOPY	Meets SAE TOPS/FOPS/FOGS requirements, left side entry cab equipped with fabric suspension seat and is adjustable forward and and comes equipped with heater, wiper, front and side opening windows. 55Z-1 is available as ZTS with zero tailswing for operation in very tight, confining areas. This design does not compromise serviceability or ergonomics of operator compartment.





Features and Benefits

Standard Equipment and Features & Benefits related to this product are subject to change without notice

Durability

A simplified, heavy duty H-frame design is enhanced by finite element analysis to create a highly durable undercarriage.

Comfort

The spacious cabs of the new generation of JCB compact excavators are easily accessed via a wide-opening door. Inside, the cabs boast ample storage, a phone tray, stowage net and cup holder, all within easy reach.

Controllability

Tracking performance is smooth and precise, enabling exceptional dozer capabilities and fast travel times. Auto kick-down motors adapt automatically to changes in terrain, for improved productivity and less operator fatigue.

Productivity

By perfectly matching the excavator boom and arm, JCB offers optimal dig-end geometry. This enables fast cycle times and dipper tearout forces of up to 6,519 lbf, for unmatched productivity.

Safety

Hose burst check valves (HBCVs) are available for the boom, dozer and arm, with an overload screen display





Prepared For:
 John Brown
 Powder Springs Public Works
 3006 Spring Industrial Drive
 Powder Springs Georgia 30127

Dealer Information
 WESPRO JCB (HL)
 918 PAUL HARRIS ROAD
 GEORGIA

Prepared By:
 JONATHAN JENKINS
 [REDACTED]
 mobile:
 Quote Date: 04/25/24
 Valid Until: 08/31/23
 Quotation Reference: 384780

phone [REDACTED]
 jbrown@cityofpowdersprings.org

Model: 55Z-1 T4 I

Qty: 1

Stock Order/Serial No:2890905

CAB WITH AIRCON: WITH TOUGHENE D GLASS
 16" (400MM) RUBBER TRACKS
 ISO/SAE CONTROL PATTERN: HIGH & LOW FLOW: DOUBLE ACTING AUX T4
 (FOR 4 WAY BLADE)
 FABRIC SUSPENSION SEAT HIGH BACK
 AMERICAN ENGLISH LANGUAGE PACK : INCLUDES BATTERY ISOLATOR,
 TRAVEL ALARM & LIVELINK
 1570MM DIPPER: HIGH AND LOW FLOW
 4 WAY DOZER BLADE: FOR 16" (400MM) WIDE TRACKS:REQUIRES HIGH
 & LOW FLOW AUX
 DOZER FLOAT: FOR MACHINES WITH OUT HYDRAULIC QUICK HITCH & 4
 WAY BLADE
 55Z-1 MIDI EXCAVATOR: TIER 4 PRIMARY BUILD
 ROTATING BEACON
 HALOGEN WORKLIGHTS: 2 FRONT & 1 REAR (BOOM LIGHT FITTED AS
 STD)(FOR A/C OR CANOPY BUILDS)
 FULL RADIO KIT:
 MECHANICAL QUICK HITCH: FOR NON HBCV MACHINES (10" (245MM) PIN
 CENTRES)
 THUMB READY DIPPER:
 GRADING BUCKET: 47" (1200MM) WIDE: NO PIVOT PINS SUPPLIED: 10"
 (245MM) PIN CENTRES: 1.8"
 1 ADDITIONAL SET OF PIVOT PINS FOR 10" (245MM) ATTACHMENTS
 Windscreen Guard
 Hydraulic Thumb

Equipment Total	84,250.00
Total Customer Sale Price	84,250.00

Optional Extras (Optional Extras are not included in the totals)

Yellow Shield - 3yr/3k Hr warranty	3,000.00
------------------------------------	----------

Notes: **Standard 2YR/2000HR Warranty Included**
 Applicable Sales Tax NOT Included
 Financing Available w/ Approved Credit
 Sourcewell Contract Number: 040319-JCB





Prepared For:

John Brown
Powder Springs Public Works
3006 Spring Industrial Drive
Powder Springs Georgia 30127

phone [REDACTED]
jbrown@cityofpowdersprings.org

Dealer Information

WESPRO JCB (HL)
918 PAUL HARRIS ROAD
GEORGIA

Prepared By:

JONATHAN JENKINS

[REDACTED]
mobile:
Quote Date: 04/25/24
Valid Until: 08/31/23
Quotation Reference: 384780

Model: 55Z-1 T4 I

Qty: 1

Customer Acceptance: _____

Date _____

Dealer _____

Date _____

